



Attorney Docket No.: 3009-1011

PATENT

IN THE U.S. PATENT AND TRADEMARK OFFICE

Applicant: HIGGS et al. Conf. No.: 4174  
Appl. No.: 10/611,982 Group: 3632  
Filed: July 3, 2003  
For: MODULAR SAFETY RAIL SYSTEM

L E T T E R

Assistant Commissioner for Patents  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

Date: December 2, 2003

Sir:

Under the provisions of 35 U.S.C. § 119 and 37 C.F.R. § 1.55(a), the applicant(s) hereby claim(s) the right of priority based on the following application(s):

| <u>Country</u> | <u>Application No.</u> | <u>Filed</u> |
|----------------|------------------------|--------------|
| GREAT BRITAIN  | 0215380.7              | July 4, 2002 |

A certified copy of the above-noted application(s) is(are) attached hereto.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 25-0120 for any additional fee required under 37 C.F.R. §§ 1.16 or 1.17; particularly, extension of time fees.

Respectfully submitted,

YOUNG & THOMPSON

By

Benoit Castel, #35,041

BC/psf

745 South 23<sup>rd</sup> Street, Suite 200  
Arlington, Virginia 22202  
(703) 521-2297

Attachment





INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 10 July 2003



*[Handwritten signature]*

- 4 JUL 2002

RECEIVED BY FAX

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



04JUL02 E730708-1 C03029  
P01/7700 0.00-0215380.7

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

KKL 25 - GB

2. Patent application number

(The Patent Office will fill in this part)

0215380.7

F4 JUL 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

KEE KLAMP LIMITED

10 WORTON DRIVE

WORTON GRANGE

Patents ADP number (if you know it)

READING

RG2 0TA

If the applicant is a corporate body, give the country/state of its incorporation

GB

7043615001

4. Title of the invention

MODULAR SAFETY RAIL SYSTEM

5. Name of your agent (if you have one)

J. R. BADGER

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

6 SIMPSON ROAD

WILDE GREEN

SUTTON COLDFIELD

WEST MIDLANDS

B72 1EP

Patents ADP number (if you know it)

949362001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

YES

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

|             |        |
|-------------|--------|
| Description | 10 /   |
| Claim(s)    | 5 /    |
| Abstract    | 1 /    |
| Drawing(s)  | 3 only |

CF

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

J. R. Badger

Date 4/7/02

12. Name and daytime telephone number of person to contact in the United Kingdom

J. R. BADGER.

0121 382 5143

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

**Patents Form 1/77**

## MODULAR SAFETY RAIL SYSTEM

This invention relates to a support foot for a modular type safety rail system and in particular, though not exclusively, to a support foot for a modular safety rail system suitable for use in providing free-standing roof edge protection.

Modular type safety rail systems are well known and typically comprise straight lengths of metal tubing inter-connected by connectors of different types such that, for example, two, three or four way inter-connections of horizontally and vertically extending tubes may be achieved.

Tubes serving as vertical posts of a safety rail, and relative to which horizontally extending tubes are connected, are supported conventionally by metal base plates. These generally need to be of a robust, heavy construction thereby to provide firm support for the vertical posts. Many different designs of base plates have been proposed, but different designs suffer different disadvantages. Thus some are relatively expensive to manufacture whilst others do not lend themselves to ease of use, for example ease of securing the vertical posts to the base plates and/or ease of securing toe boards of different sizes or in different orientations. Other designs do not lend themselves readily to being stacked safely in a manner which is inherently adapted to resist toppling of the stacked assembly.

The present invention seeks to provide an improved support foot for a modular safety rail system in which at least some of the aforescribed disadvantages of known base plates are mitigated or overcome. The invention seeks also to provide also a safety rail assembly comprising a plurality of said support feet.

In accordance with one aspect of the present invention there is provided a support foot for a modular safety rail system, said support foot being adapted

to provide location for a vertical member of the safety rail system and to provide location for a toe board which may be arranged, in use, to extend between two successive, spaced apart support feet, each said support foot comprising:-

a base plate having upper and lower surface regions and an outer periphery;

a plurality of location formations positioned inwards of said outer periphery and each extending from said upper surface for location of a vertical member;

a plurality of web formations provided at said upper surface and each extending from a respective location formation in a direction towards said outer periphery, each web formation extending from the upper surface of the base plate to an upper edge of the web formation;

the lower surface of the base plate having at least one recess region shaped and positioned such that when one said support foot is stacked on top of a second said support foot (a) at least one of a distal end of a location formation and an upper edge of a web formation of said second said support foot engages with said recess region of said one said support foot to prevent lateral movement of said one said support foot relative to said second said support foot, and (b) the upper edge of each said web formation of said second said support foot is able to be contacted by the lower surface of said one said support foot thereby to resist toppling of the superimposed support foot.

In addition to being able to resist toppling of superimposed support feet, the upper edge of each of at least some of the web formations may be employed to support the weight of superimposed support feet. Alternatively, or



additionally, the distal end of a, more preferably each, location formation may be employed to support the weight of superimposed support feet.

The invention envisages that preferably the support foot comprises at least three support webs, each of the support webs preferably being uniformly spaced apart. In a preferred embodiment of the invention the support foot comprises four support webs each extending in a direction substantially perpendicular relative to the two support webs between which it is positioned. In the case of a support plate having four webs, two successive webs preferably have the support surfaces thereof facing in an anti-clockwise direction whilst the other two webs have the support surfaces thereof facing in a clockwise direction.

The invention further teaches that preferably each location formation will have a web formation associated therewith, but it does not exclude the possibility of one or more additional location formations devoid of an associated web formation. Preferably each web formation is arranged to provide structural support for, and be supported by, a location formation.

Each location formation typically may be in the form of a socket having a central, typically cylindrical, bore which in use receives an end of a vertical post comprised by for example a rigid rod or tube. A location formation may be provided with retention means, such as a screw threaded aperture for receiving a grub screw which may be tightened to engage with the outer surface of a rod or tube inserted into the socket formation thereby to enable the vertical member to be positively located axially, in a vertical direction, relative to the support foot. Another suitable type of retention means comprises a hole, preferably a pair of diametrically opposite holes, in the wall of a location formation such that a retention pin may be inserted through the location formation and through one or a pair of aligned holes of an inserted

vertical member. The pin may comprise a toggle device to inhibit inadvertent removal.

It is further preferred that the distal ends of the location formations extend further from the base plate than the web formations, and that the lower surface of the base plate is provided with one or a plurality of individual recesses to accommodate the distal ends of the location formations in a manner in which, when one support foot is stacked on top of another, relative lateral movement of the two support feet is restrained by the presence of the distal ends of the location formations in said recess or recesses. Alternatively or additionally the base plate may have at least one recess for engagement by the upper edge surface region of a web formation to restrain said relative lateral movement.

The weight of the upper of a pair of vertically aligned support feet may be supported by upper surfaces of the web formations of the lower of the two support feet. Alternatively, said weight may be supported normally by the distal end of the or each location formation of the lower of the two support feet, in which case the upper surfaces of the web formations will lie slightly spaced from the lower surface of the superimposed foot but be contacted by that surface to resist toppling if the stack departs from a truly vertically aligned condition. Preferably said spacing is sufficiently small to ensure that there is resistance to toppling of a stack of at least five said support feet, more preferably a stack of at least ten said support feet.

Preferably said upper edge of a web formation is available to provide support for a superimposed second support foot at a position of that upper edge which lies furthest from the associated location formation, preferably at a position substantially aligned with the outer periphery of the base plate thereby to assist in providing good resistance to relative toppling movements.

A web formation may be provided with retention means for enabling a toe board to be secured thereto. A web formation may be provided with an aperture to enable a toe board to be secured to the web formation by a screw or nut and bolt assembly. Additionally or alternatively a toe board may be located relative to the support foot by engaging in a slot provided in the base plate of the support foot, with a face of the web formation lying adjacent an edge of the slot thereby to provide a support function for the toe board.

Preferably a slot in the base plate extends for only part of the distance from the outer periphery of the base plate towards a location formation such that, if desired, instead of the toe board being located in the slot and thus resting directly on the same roof or ground surface as that on which the support rests, the toe board may be supported elevated above the roof or ground surface by a distance corresponding to the thickness of the base plate. To enable greater than average thickness toe boards to be secured to a web formation in a slightly elevated position, with the base of the toe board resting on the upper surface of the base plate, it is preferred that a web formation is provided at only one side of the slot. The upper surface of the base plate may be provided with one or more handle formations to enable the support foot readily to be lifted for transportation.

The base plate, location formations, web formations and any handle formations preferably may be formed integrally with one another, for example in the form of a casting of iron or other metal. However, for example, a part of the support foot, such as a handle, may be pre-forged and then integrated with the remainder of the foot during a casting operation.

Each web formation preferably is formed integral with a location formation over a substantial part of the distance for which the location formation extends from the upper surface of the base plate thereby to provide a stiffening or other strengthening of the location formation. In turn, each web formation

may be provided with a reinforcing formation, at a side opposite that face of the web formation which in use is contacted by a toe board thereby to enhance the resistance of the web formation to sideways, bending movement under action of the toe board.

The base plate typically is of substantially uniform thickness, and also typically has upper and lower surfaces which are substantially planar. The outer periphery may be circular, but other peripheral shapes such as square or polygonal are not excluded from the scope of the invention.

The support foot of the present invention exhibits a high degree of strength and rigidity in a construction which avoids excessive use of materials and is relatively well adapted to manufacture by, for example, a casting technique. Importantly, the construction also facilitates a plurality of the support feet to be stacked one on top of another in a substantially stable configuration in which relative lateral movement is resisted by location of the distal ends of the location formations in the recesses of the lower surface of an adjacent support foot, and in which the lower surface of a superimposed support foot is well supported, or supportable, close to the outer periphery thereof by the outer regions of the upper edges of the web formations of the underlying support foot.

One embodiment of the present invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which:-

Figure 1 is a perspective view of the upper part of a support foot in accordance with the present invention;

Figure 2 is a perspective view of the underneath of the support foot of Figure 1, and

Figure 3 is a perspective view of a modular safety rail installation comprising a plurality of support feet each in accordance with the present invention.

A cast iron support foot 10 for a modular safety rail system comprises a base plate portion 11 which is generally of a disc type shape comprising an upper surface 12, a lower surface 13 and an outer periphery defined by a substantially cylindrical edge 14.

The base plate 11 is of a substantially planar form having a uniform thickness except that, as described in more detail below, the lower surface 13 is provided with recesses and the upper surface 12 has a plurality of portions which are integral with the base plate and extend therefrom.

The upper surface 12 is provided, near to but spaced from the centre thereof, with four location formations each adapted for location of a vertical post. Each location formation is in the form of a socket 15 having a through-bore 16. The four sockets 15 are uniformly circumferentially spaced about the major axis of said cylindrical edge surface 14. Each socket is provided with a screw threaded aperture 17 for a grub screw (not shown) which can be tightened to bear against the outer surface of a vertical post inserted in the bore 16 thereby to secure that post against rotation or longitudinal movement relative to the socket. (In an alternative embodiment, not illustrated, the socket may be provided with a pair of diametrically opposite holes and a pin with a toggle end retainer is inserted through those holes and a pair of pre-formed holes in the end of a post to provide said location).

Each socket 16 provides support for and is in part supported by a web 18 that extends radially outwards from the socket to the outer cylindrical edge

surface 14. The web is a very substantially planar form and lies in a plane perpendicular to the upper surface 12 of the base plate 11.

Each web 18 has an upper edge surface 19 which extends parallel with the base plate surface 12 and lies spaced from said surface 12 by a distance slightly less than the spacing from said surface 12 of the distal end 20 of the socket 15. The upper edges 19 of the four webs all lie at the same height from the base plate surface 12. Similarly, the distal ends 20 of the sockets all lie at the same spacing from the surface 12.

The web formations 24 are provided in an asymmetric configuration in which as viewed in Figure 1, two successive webs 18 have the support surfaces 24 thereof facing in an anti-clockwise direction whilst the other two webs have the support surfaces 24 thereof facing in a clockwise direction. In consequence, when two of the support feet are arranged spaced apart with two web formation of one support foot aligned substantially with two webs of the other support foot, the web support surface of one support foot at one end of the toe board faces in the same direction as the web support surface of the support foot at the other end of the toe board.

Each web is provided with an aperture 21 to allow a toe board of a safety rail installation to be bolted to that web.

In addition to the support which each socket 15 provides for an associated web 18, each web is supported by a reinforcing rib 22 at that surface of the web opposite that to which it is intended that, in use, a toe board is to be secured and supported.

The base plate comprises four uniformly circumferentially spaced slots 23 each lying adjacent a respective web support surface 24. Each slot 23

extends radially inwards towards a socket 15 for a distance substantially equal to two thirds of the radial length of the web 18.

In addition to the sockets and webs the upper surface 12 has three handle formations 25 extending therefrom. The central handle typically is for use by a crane hook, and the end handles enable two persons to move the foot manually. Each handle 25 extends to a maximum distance from the upper surface 12 of the base plate which is less than the spacing of the web upper edge surface 19 from the base plate surface 12. The base plate additionally comprises three slots 26 each aligned with and positioned underneath a respective one of the handles 25. (In an alternative embodiment, the end handles are each disposed generally perpendicular to the illustrated position and close to the edge 14; to increase their robustness when in that orientation where there are potentially more exposed to damage they may be of a pre-forged type).

The lower surface 13 of the base plate comprises four recess regions 27 each aligned with a respective one of the socket through-bores 16. Each recess 27 has a depth slightly less than the distance by which the distal end 20 of each socket extends beyond the upper edge surface 19 of an associated web. When a plurality of the support feet are stacked one on top of another, the distal ends 20 of the sockets can be orientated to lie in the recesses thereby to restrain relative lateral movement of two successive support feet. In addition, in that stacked configuration, each superimposed support foot has the lower surface thereof support by the distal ends 20 of the sockets 15. The upper edges 19 of the webs then lie close to but slightly spaced from the superimposed foot so that they can be contacted by that foot to provide a resistance to toppling if the superimposed foot is caused to depart from a truly vertically aligned position. The webs are able to provide that support at radially outer positions substantially aligned with the outer cylindrical edge 14

of the base plate 11 and thereby are particularly effective to offer stable support and resistance to toppling of a stacked plurality of the support feet.

In the safety rail assembly shown in Figure 3 four of the aforedescribed support feet 10 are employed to support six vertical posts 30. Upper horizontal rails 31 and mid-height horizontal rails 32 extend between the posts of each successive pairs of posts and are connected to the vertical posts in known manner by 90° connectors 33 and T connectors 34. The support feet are orientated such that two of the web formations of each support foot lie parallel with two web formations of a successive support foot. In consequence a toe board 35 (one only illustrated for clarity) can be secured to the co-planar faces of web formations of two successive support feet arranged at the respective ends of the board 35.

KKL25DE1



## Claims

**1. A support foot for a modular safety rail system, said support foot being adapted to provide location for a vertical member of the safety rail system and to provide location for a toe board which may be arranged, in use, to extend between two successive, spaced apart support feet, each said support foot comprising:-**

**a base plate having upper and lower surface regions and an outer periphery;**

**a plurality of location formations positioned inwards of said outer periphery and each extending from said upper surface for location of a vertical member;**

**a plurality of web formations provided at said upper surface and each extending from a respective location formation in a direction towards said outer periphery, each web formation extending from the upper surface of the base plate to an upper edge of the web formation;**

**the lower surface of the base plate having at least one recess region shaped and positioned such that when one said support foot is stacked on top of a second said support foot (a) at least one of a distal end of a location formation and an upper edge of a web formation of said second said support foot engages with said recess region of said one said support foot to prevent lateral movement of said one said support foot relative to said second said support foot, and (b) the upper edge of each said web formation of said second said support foot is able to be contacted by the lower surface of said one said support foot thereby to resist toppling of the superimposed support foot.**

2. A support foot according to claim 1, wherein the distal ends of the location formations extend further from the base plate than the web formations.

3. A support foot according to claim 2, wherein the lower surface of the base plate is provided with one or a plurality of individual recesses to accommodate the distal ends of the location formations in a manner in which, when one support foot is stacked on top of another, the weight of the upper of a pair of support feet is supported by the distal end of at least one of said location formations of the lower of the two support feet, with relative lateral movement of the two support feet being restrained by the presence of the distal ends of the location formations in said recess or recesses.

4. A support foot according to claim 3, wherein when one support foot is stacked on top of another a spacing exists between the upper edge surfaces of the web formations of the lower support foot and the lower surface of the upper of the two support feet.

5. A support foot according to claim 2 or claim 3, wherein the lower surface of the base plate is provided with one or a plurality of individual recesses to accommodate the distal ends of the location formations in a manner in which, when one support foot is stacked on top of another, the weight of the upper of a pair of support feet is supported by upper edge surfaces of the web formations of the lower of the two support feet, with relative lateral movement of the two support feet being restrained by the presence of the distal ends of the location formations in said recess or recesses.

6. A support foot according to any one of the preceding claims, wherein upper edge surfaces of the web formations are each able to provide support for a superimposed second support foot at a position of that upper edge which lies furthest from the associated location formation.

7. A support foot according to claim 6, wherein said upper edge surfaces are each able to provide support for a superimposed second support foot at a position substantially aligned with the outer periphery of the base plate.

8. A support foot according to any one of the preceding claims, wherein the support foot comprises at least three support webs.

9. A support foot according to any one of the preceding claims, wherein the support foot comprises four support webs each extending in a direction substantially perpendicular relative to the two support webs between which it is positioned.

10. A support foot according to claim 9, wherein two successive webs have the support surfaces thereof facing in an anti-clockwise direction and the other two webs have the support surfaces thereof facing in a clockwise direction.

11. A support foot according to any one of the preceding claims, wherein each web formation provides structural support for, and is supported by, a location formation.

12. A support foot according to any one of the preceding claims, wherein each location formation comprises a socket having a central cylindrical bore which in use receives an end of a vertical member, and retention means to enable the vertical member to be positively located axially, in a vertical direction, relative to the support foot.

13. A support foot according to any one of the preceding claims, wherein the base plate comprises a slot adapted to receive a part of a toe board and the face of a web formation lies adjacent an edge of the slot thereby, in use, to provide a support function for a toe board positioned in said slot.

14. A support foot according to claim 13, wherein the slot extends for only part of the distance from the outer periphery of the base plate towards a location formation.

15. A support foot according to any one of the preceding claims, wherein the base plate, location formations, and web formations are formed integrally with one another in the form of a casting.

16. A support foot according to any one of the preceding claims, wherein each web formation is formed integral with a location formation over a substantial part of the distance for which the location formation extends from the upper surface of the base plate.

17. A support foot according to any one of the preceding claims, wherein each web formation is provided with a reinforcing formation, at a side opposite that face of the web formation which in use is contacted by a toe.

18. A support foot according to any one of the preceding claims, wherein the outer periphery of the base plate is circular.

19. A support foot according to claim 1 and substantially as hereinbefore described.

20. A modular safety rail assembly comprising a plurality of support feet in accordance with any one of the preceding claims.

KKL25CL1GB

## ABSTRACT

## MODULAR SAFETY RAIL SYSTEM

A support foot for a modular safety rail system comprises a base plate having upper and lower surfaces and an outer periphery, a plurality of sockets positioned inwards of said periphery and extending from said upper surface for location of a vertical post, a plurality of webs provided at said upper surface and each extending from a socket towards said periphery, each web extending from the base plate to an upper edge surface of the web, the lower surface of the base plate having at least one recess whereby when one support foot is stacked on top of another at least one of a distal end of a socket and an upper edge of a web engages the recess to prevent lateral movement of the feet, and the upper edge surface of each web being able to support the lower surface of a superimposed support foot to resist toppling.

RK25AB1




FIG. 1








FIG. 2






FIG. 3

Document filed by:

Young & Thompson

745 South 23rd Street

Arlington, Virginia 22202

Telephone 703/521-2297

SN 10/611, 982 E.L. July 3, 2003